

Hoja de Datos

Mezclar / Agitadores Magnéticos



Midi MR 1 digital IKAMAG®

Potente agitador magnético sin calefacción.

- Carcasa de acero inoxidable plana y de gran estabilidad
- Motor a prueba de bloqueo
- Velocidad regulable sin interrupciones
- Indicador digital (LED) de velocidad
- Temporizador de 0 a 56 min con conexión permanente
- Cantidad agitada hasta 50 litros (H2O)

Accesorios: IKAFLON® 50 Set (5 Pcs) slide round PTFE-coated Magnetic stirring bars, TRIKA® 55 Set (5 Pcs) PTFE-coated Magnetic stirring bars, TRIKA® 40 Set (5 Pcs) PTFE-coated Magnetic stirring bars, TRIKA® 25 Set (5 Pcs) PTFE-coated Magnetic stirring bars, IKAFLON® 125 (1 Pc) beaker PTFE-coated Magnetic stirring bars, IKAFLON® 25 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® 40 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® 50 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® 80 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® glass 25 Set (5 Pcs) round Magnetic stirring bars, IKAFLON® glass 30 Set (5 Pcs) round Magnetic stirring bars, IKAFLON® glass 40 Set (5 Pcs) round Magnetic stirring bars, IKAFLON® glass 50 Set (5 Pcs) round Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) power SmSo PTFE-coated Magnetic stirring bars, IKAFLON® 50 Set (5 Pcs) power SmSo PTFE-coated Magnetic stirring bars, IKAFLON® 25 Set (5 Pcs) slide round PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) slide round PTFE-coated Magnetic stirring bars, IKAFLON® 40 Set (5 Pcs) slide round PTFE-coated Magnetic stirring bars, TRIKA® 80 Set (5 Pcs) PTFE-coated Magnetic stirring bars, IKAFLON® 25 Set (5 Pcs) ellipse PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) ellipse PTFE-coated Magnetic stirring bars, IKAFLON® 35 Set (5 Pcs) ellipse PTFE-coated Magnetic stirring bars, IKAFLON® 40 Set (5 Pcs) ellipse PTFE-coated Magnetic stirring bars, IKAFLON® 50 Set (5 Pcs) ellipse PTFE-coated Magnetic stirring bars, IKAFLON® 60 Set (5 Pcs) ellipse PTFE-coated Magnetic stirring bars, IKAFLON® 70 Set (5 Pcs) ellipse PTFE-coated Magnetic stirring bars, IKAFLON® 25 Set (5 Pcs) cross PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) cross PTFE-coated Magnetic stirring bars, IKAFLON® 38 Set (5 Pcs) cross PTFE-coated Magnetic stirring bars, IKAFLON® 37 Set (5 Pcs) bone PTFE-coated Magnetic stirring bars, IKAFLON® 54 Set (5 Pcs) bone PTFE-coated Magnetic stirring bars, IKAFLON® 67 (1 Pc) beaker PTFE-coated Magnetic stirring bars, IKAFLON® 74 (1 Pc) beaker PTFE-coated Magnetic stirring bars, IKAFLON® 103 (1 Pc) beaker PTFE-coated Magnetic stirring bars, H 11 Cable de alimentación USA , H 11 Cable de alimentación enchufe EURO, RSE Extractor de varillas agitadoras, H 11 Cable de alimentación enchufe CH, H 11 Cable de alimentación enchufe Euro

Información Técnica

Número de puestos de agitación	1
Max. cantidad a agitar por cada posición (H2O) [l]	50
Potencia del consumo del motor [W]	70
Potencia del suministro del motor [W]	19
Indicador de velocidad	LCD
Rango de velocidad [rpm]	0 - 1000
Longitud max. varilla magnética [mm]	80
Material de la superficie de la placa	acero inoxidable 1.4301
Dimensiones de la superficie de la placa [mm]	350 x 350
Dimensiones (An x Al x Pr) [mm]	360 x 110 x 430
Peso [kg]	10.7
Temperatura ambiental permitida [°C]	5 - 40
Humedad relativa permitida [%]	80
Clase de protección de acuerdo al DIN EN 60529	IP 21
Voltaje [V]	230 / 100 - 120
Frecuencia [Hz]	50/60
Consumo de energía [W]	70

No. ref. 0002621901