

Hoja de Datos

Mezclar / Agitadores Magnéticos



RO 10

10-position digital magnetic stirrer without heating, designed for synchronous stirring. The magnetic coil technology provides noiseless and consistent stirring on all positions. Speed remains constant, even when load changes. The closed and compact design allows easy cleaning and protects the equipment against the penetration of liquids. Additionally, a removable transparent anti-slip mat is included.

- Adjustable reverse operation
- Wear free magnetic coils
- Error code display
- Easy operation with touch keypad
- Suitable for continuous operation
- Adjustable speed in increments of 10 rpm

Accesorios: IKAFLON® 15 Set (5 Pcs) power SmSo PTFE-coated Magnetic stirring bars, IKAFLON® 9 Set (5 Pcs) crown PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) cross PTFE-coated Magnetic stirring bars, IKAFLON® 25 Set (5 Pcs) cross PTFE-coated Magnetic stirring bars, IKAFLON® 20 Set (5 Pcs) cross PTFE-coated Magnetic stirring bars, IKAFLON® 10 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® 15 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® 20 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® 25 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) round PTFE-coated Magnetic stirring bars, IKAFLON® glass 25 Set (5 Pcs) round Magnetic stirring bars, IKAFLON® glass 30 Set (5 Pcs) round Magnetic stirring bars, TRIKA® 25 Set (5 Pcs) PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) power SmSo PTFE-coated Magnetic stirring bars, IKAFLON® 25 Set (5 Pcs) slide round PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) slide round PTFE-coated Magnetic stirring bars, IKAFLON® 20 Set (5 Pcs) ellipse PTFE-coated Magnetic stirring bars, IKAFLON® 25 Set (5 Pcs) ellipse PTFE-coated Magnetic stirring bars, IKAFLON® 30 Set (5 Pcs) ellipse PTFE-coated Magnetic stirring bars, IKAFLON® 10 Set (5 Pcs) cross PTFE-coated Magnetic stirring bars, H 11 Cable de alimentación USA , H 11 Cable de alimentación enchufe EURO, RSE Extractor de varillas agitadoras, H 11 Cable de alimentación enchufe CH, H 11 Cable de alimentación enchufe Euro

Información Técnica

Número de puestos de agitación	10
Max. cantidad a agitar por cada posición (H2O) [l]	0.4
Distancia entre puestos de agitación [mm]	90
Desviación de velocidad individual por cada puesto [%]	0
Max.cantidad a agitar (H2O) [l]	4
Indicador de velocidad	línea del LED
Rango de velocidad [rpm]	0 - 1200
Longitud max. varilla magnética [mm]	30
Control de velocidad	10 pasos de RPM
Material de la superficie de la placa	acero inoxidable 1.4301
Dimensiones de la superficie de la placa [mm]	190 x 470
Dimensiones (An x Al x Pr) [mm]	190 x 60 x 570
Peso [kg]	5
Temperatura ambiental permitida [°C]	5 - 40
Humedad relativa permitida [%]	80
Clase de protección de acuerdo al DIN EN 60529	IP 40
Voltaje [V]	100 - 240
Frecuencia [Hz]	50/60
Consumo de energía [W]	25
Voltaje DC [V=]	24

No. ref. 0003691000